



# 15.47m Tri Axle Skeletal Box Body Spec Sheet



**T  
R  
A  
I  
L  
E  
R  
S**

Trailer:	Skeletal trailer specifically designed for optimum payload serving the cold distribution and dry-freight industries
Chassis:	<ul style="list-style-type: none"> <li>• Fabricated I-beam manufactured to the highest standards</li> <li>• Combination of 8mm &amp; 4mm Domex 700 webbing</li> <li>• 10mm Domex 700 bottom flange, 8mm Domex 700 top flange</li> <li>• 6mm Domex 700 halfround cross members for improved flexibility and strength</li> </ul>
Axles:	• BPW Ecoplus 3
Suspension:	• BPW Air Suspension
Landing Gear:	• BPW M-900 roll type
Kingpins:	• Jost KZ 1008 removable kingpins
Toolbox:	• BPW Poly-ethylene 800mm side mounted toolbox
Brake System:	• Wabco ABS brake system with "Tasc" valve fitted to SABS standards
Rims:	• ALCOA 22,5x11,75 10 Stud 0mm offset brushed aluminium
Tyres:	• 6 x 385/65R22.5 Tubeless
Sparewheel:	• 1 x 385/65R22,5 on rim fitted on spare wheel carrier
Underrun Bumper:	• 160mm x 80mm x 4mm Rectangular tubing rear underrun bumper manufactured to SABS specifications
Lightboxes:	<ul style="list-style-type: none"> <li>• 160mm x 80mm x 4mm Rectangular tubing removable lightboxes fitted with LED lamps</li> <li>• Angled outside lights for better visibility</li> </ul>
Paint:	• All steel chemically cleaned, primered and finidhes in the colour of choice

